

Atlas Copco Portable Air Compressors



XA(T,V)S 400 JD iT4

The next big thing is small.

Atlas Copco is a leading manufacturer of portable air compressors in the world. Atlas Copco has developed air compressors that successfully walk the line between size, output and capacity and are designed for a wide variety of applications.



Tier⁺4 Interim
Compliant with the new EPA emission regulations of 2012

Sustainable Productivity

Atlas Copco

The options you need for all your specific applications.

These portable compressors are workhorses. Featuring Atlas Copco's new C111 element for improved compression efficiency, the XAS 400 JD iT4 is ideal for demanding applications including sandblasting and pipe maintenance. The XC 2002 control module with LCD display puts integrated engine electronics for performance and diagnostics at your fingertips.



- Extremely reliable John Deere power with optional 5 year engine warranty
- Interim Tier 4 exhaust emission compliance
- Operates under widely varying climatic conditions, water-cooled engine, large capacity oil cooling system, high efficiency heavy-duty two-stage intake filters (with cartridge replacement indicators)
- Highly efficient oil extraction system means low oil consumption
- Large capacity fuel tank placed low for good road handling and easy filling
- Gull wing doors for easy access to engine and components
- Variable speed clutch fan for optimal cold weather operation
- Comes standard with Canadian Cold Weather package; HD battery, block heater, synthetic oil
- Optional aftercooler / water cooler & filtration system for cool, dry & clean air

Atlas Copco Compressors LLC
 Rock Hill Product Company
 1800 Overview Drive
 Rock Hill, SC 29730
 www.atlascopco.us

Technical data

Type		XAS 400 JD iT4	XATS 400 JD iT4	XAVS 400 JD iT4
Normal effective working pressure	psi	100	150	200
	bar	7	10	14
Maximum unloading working pressure	psi		58	
	bar		4	
Actual free air delivery	cfm		406	
	l/sec		185	
Cooling system			Air / Oil	
Oil Capacity	US gal.		6.3	
	Liter		23.8	

Engine - John Deere		
Model number	4045HFC92	
Engine Emissions	iT4	
Cooling system	PARCOOL EG	
Number of cylinders	4	
Capacity of oil sump	US gal.	1.8
	Liter	6.8
Capacity of fuel tank	US gal.	58
	Liter	219
Engine speed (maximum loaded)	rpm	2400
Engine speed (unloaded)	rpm	1500

Unit dimensions (L x W x H)		
Trailer mounted	inch	152 x 72 x 69
	m	3.86 x 1.83 x 1.75
Support mounted	inch	104 x 55 x 62
	m	2.64 x 1.40 x 1.57

Weight		
Trailer mounted - Wet	lbs	4105
	kg	1862
Support mounted - Wet	lbs	4225
	kg	1916

*complies with 2000/14/EC, 84/533/ECC AND 85/406/EEC limits

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.



Never use compressed air as breathing air without prior purification in accordance with local legislation and standards.

www.atlascopco.com